

65W Series Power Supply

D65-Desktop Type
12-24V 5A MAX. 65W



SAFETY APPROVALS | CE, FCC

FEATURES

100-240VAC Universal Input
Meet CEC, Energy Star 2.0 (Level V)
3 Years Warranty

Model	O/P Voltage	O/P Current	Watt	Model	O/P Voltage	O/P Current	Watt
D65 120004000	12.0V	4A	48W	D65-150004000	15.0V	4A	60W
D65 120004160	15.0V	4.16A	50W	D65-240002500	24.0V	2.5A	60W
D65 120005000	12.0V	5A	60W				

INPUT CHARACTERISTICS

Rated Input Voltage 100-240V AC
 Rated Frequency 50/60Hz
 Steady AC Current 1.5A(Max) Measured at 100Vac input and maximum load
 Inrush Current Less than 80A
 Empty Loaded Wasting 500mW

OUTPUT CHARACTERISTICS

Power 60W MAX
 Load Regulation ±5%
 Turn on delay time 3s Max at AC 115V, Max output load
 Hold up time 5ms Min at AC 115V, Max output load
 Rise up time 40ms Max at AC 115V, Max output load
 Efficiency Meet CEC, Energy Star 3.0 (EPA/DOE—Level VI)

SAFETY STANDARDS

LVD UL62368-1/UL60950-1
 IEC62368-1/IEC60950-1 EN62368-1
 EMC & EMI EN55032 EN55024 EN61000-3-2 EN61000-3-3

PROTECTION

Over Voltage Protection Auto Recovery
 Short Circuit Protection Auto Recovery
 Over Current Protection Auto Recovery
 Protection Class Class I

RELIABILITY ITEMS

Hi-Pot Test AC 3000V1min between input plug-DC plug
 Leakage Current 3.5mA max at nominal AC input voltage and frequency
 Temperature Rise Case surface rise 95°C or less

ENVIRONMENTAL

Operation Temperature -10 °C – 40 °C
 Storage Temperature -25 °C – 70 °C
 Operation Humidity 5%(0°C) ~ 90%(40°C)
 Storage Humidity 5%~ 95%

MECHANICALS				
Cable UL2464#20AWG, 1750mm	Case Material UL94-V1	IEC-320-C14	Case Dimension	Weight
			L115*W51*H30mm	210g (Ref.)